



1832 N Glassell St · Orange, California 92865
1-888-MINIPAC · www.vac-smart.com

MV 65 VacSmart™ – Chamber Vacuum Sealer with Advanced HACCP Features



MV 65 VacSmart™ – Chamber Vacuum Sealer with Advanced HACCP Features

FEATURES

- Seamless stainless chamber 29" x 27"
- Height: 5" (Chamber) + 5.5" (Lid) = 10.5"
- Quick release seal bars at 26" length
- Transparent lid for operator viewing
- 304 stainless steel construction
- Shatterproof lid hinge design
- Full-color sealed LCD touch display
- Ethernet, USB, and Thermocouple connectivity
- TruVac™ sensors for hold + vacuum pulse infusion
- Flippin' Tray for unique food shapes, sizes & liquids

SOFTWARE

- 6 speed keys
- 999+ product look-ups
- Selectable vacuum display in mbar or %
- HACCP Plan included at www.HACCP-Portal.com
- Fragile food protection with controlled air return

ADVANCED HACCP FEATURES

- E-data reporting with PDF file download
 - Operator, product, date/time, batch number
 - County of origin, supplier information, pH level, temperature
 - Immediate corrective action entry at vacuum machine
- Sanitation alerts
 - Food type change (i.e. beef - fish - beef)
 - 4-hour operation sanitation prompt
 - Air dry sanitation instructions
- Programmable label printer (optional)
 - Product name, packed date and use by date
 - Ingredients, product handling message, operator name
 - Sequential number, address, barcode, etc.

MODELS

- MV 65 VacSmart™ Left & Right Seal Bars



MV 65 VacSmart

OPTIONS

- 220 volts, 50-60 Hz, single phase, 22 amps, 63 m³/h
- 208 volts, 50-60 Hz, 3-phase, 25 amps, 100 m³/h
- Inert gas kit - N₂/CO₂/AR injection (8 nozzles)
- Round seal + excess bag trimmer



1832 N Glassell St · Orange, California 92865
 1-888-MINIPAC · www.vac-smart.com


MV 65 VacSmart™ – Chamber Vacuum Sealer with Advanced HACCP Features




MV 65 VacSmart™ – Chamber Vacuum Sealer with Advanced HACCP Features

ACCESSORIES

- 1. Direct thermal label printer (203 dpi)
- 2. Water-resistant flexible keyboard
- 3. Inkjet printer for HACCP reporting
- 4. K-Type needle temperature probe
- 5. Volume plates - replaces Flippin' Tray
- 6. 2.5 quart aeration & food storage box




1




2



3



4



5



6

TECHNICAL SPECIFICATIONS

- Linux embedded operating system
- 5" LCD touch screen display, resistive type
- ARM Cortex A7 quad-core processor
- 1GB LPDDR2 RAM memory
- 8GB microSD storage
- WiFi & Bluetooth connectivity
- 10/100 Mbps Ethernet port
- Two USB 2.0 ports
- Two thermocouple ports

POWER

- 63 m³/h Busch® vacuum pump
- 208 volts, 50-60 Hz, 3-phase
- 19 amps

SHIPPING

- Shipping dimensions 36" x 39" x 51"H
- Shipping weight 579 lbs

DETAILS AND DIMENSIONS

- A = 32.25" (820 mm)
- B = 41" (1045 mm)
- C = 36.5" (930 mm)
- D = 36.25" (923 mm)
- E = 58.25" (1480 mm)

