



56 MPE Grey





Sealing Area	
Maximum Product Height	9.45"
Maximum Product Length	21.75"
Center Folded Film Types	Supports any film type
Maximum Roll Width	28"
Maximum Roll Diameter	12"
Adjustable Product Height	✓
Teflon Coated Sealing Blade	✓
Programmable Sealing Blade Temperature	✓
Performance	
Wraps per Minute*	30-50 items
External Pneumatic Seal Pressure Required	-
AC Servo Motor Driver	✓
Power Supply	230V / 1ph / 13A
Display & Controls	
Water Resistant Digital Display	Touch Screen
Control Board	PLC Schneider®
User-Settable Programs	Unlimited
Operational Features	
Machine Type	Automatic L-Sealer
Sealing Technology	Center Sealer
Motors	Non-pneumatic Servo Motors
Access	Two Gull-Wing Doors for Easy Access
Controls	Large Touch Screen Control Panel
Belt	Food-Approved Belting
Automatic: Seal»Cut»Release»Advance	√
Sealing Blade Heat	Constant
Photo Cell Activation	✓
Auto-Entry Conveyer	✓
Auto-Discharge Conveyer	✓
Conveyor Belt Modes	Continuous / Step- Advance
Programmable Conveyer Speed	✓
Small Product Kissing Belt	√
Overheat Safety Circuit	✓
Automatic Waste Winder	✓
No Moving Parts Exposed	✓
Tearless Perforation System	✓
Patented Safety System	✓
Service	
Easy Frontal Access	✓
Indicating Display	✓
Operating/Running/Problem Light	✓
Error Codes	✓
1 Year Limited Warranty	✓
Housing & Dimensions	Otral/Pal 15
Material	Steel / Baked Enamel
Width x Length	97.75" x 49"
Height (Lid open/closed)	77" / 68"
Working Height	34"
Locking Casters	√
Shipping Weight	1540lbs
Optional Features	
Irregular Shape Stabilizer Kit	✓
Single Hole Punch	✓
Narrow Product Kit	✓
Depends on type of product, film and operator ability	

^{*}Depends on type of product, film and operator ability. Specifications may change without notice.