



## **Twin Tunnel 50**



Heating Area	
Tunnel Inlet	15.75" x 7.5"H
Tunnel Length	44.75"
Shrink Film Types	All
Performance	
Tunnel Heater Wattage	14KW
Power Supply	208V / 3ph / 35A
Display & Controls	
Water Resistant LED Display	<b>✓</b>
Digital Display	1
Customizable Programs	9
Operational Features	
Programmable Conveyor Speed	1
Adjustable Air Flow	<b>✓</b>
Automatic Cool-Down	1
Adjustable Conveyer Height	1
Self-Rotating Conveyor Rolls	<b>✓</b>
Double-Insulated Walls	✓
18" Exit Roll Conveyor	✓
Service	
Easy Frontal Access	✓
Indicating Display	✓
Error Codes	✓
1 Year Limited Warranty	✓
Housing & Dimensions	
Material	Steel / Baked Enamel
Machine Size (W x L x H)	67.91" x 31.5" x 60.43"
Working Height	34"
Locking Casters	1
Weight (Net/Shipping)	572 lbs / 701 lbs
Optional Features	
Teflon Belt	1

Specifications may change without notice.





## **Twin Tunnel 50 Stainless Steel**



Heating Area	
Tunnel Inlet	15.75" x 7.5"H
Tunnel Length	44.75"
Shrink Film Types	All
Performance	
Tunnel Heater Wattage	14KW
Power Supply	208V / 3ph / 35A
Display & Controls	
Water Resistant LED Display	1
Digital Display	✓
Customizable Programs	9
Operational Features	
Programmable Conveyor Speed	1
Adjustable Air Flow	✓
Automatic Cool-Down	1
Adjustable Conveyer Height	1
Self-Rotating Conveyor Rolls	1
Double-Insulated Walls	1
18" Exit Roll Conveyor	1
Service	
Easy Frontal Access	1
Indicating Display	1
Error Codes	1
1 Year Limited Warranty	✓
Housing & Dimensions	
Material	Stainless Steel
Machine Size (W x L x H)	67.91" x 31.5" x 60.43"
Working Height	34"
Locking Casters	1
Weight (Net/Shipping)	572 lbs / 701 lbs
Optional Features	
Teflon Belt	/
Specifications may change without notice	

Specifications may change without notice.